

# 301-CI9401-0500

# **Multi-Conductor – Shield Twisted Pair Cable**







# **DECRIPTION**

18 AWG stranded (16x30) tinned copper conductor, polyethylene insulation, twisted pair, aluminum shield (125% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.

#### **APPLICATION**

Multipair Audio, Control and Instrumentation Cable for Industrial, Data, Interconnect and Analogue Audio used.

#### PHYSICAL CHARACTERISTICS

#### Conductor

#### **AWG**

Pair	AWG	Stranding	Conductor Material
1	18	16x30	TC – Tinned Copper

#### Insulation

#### **Insulation Material**

Insulation Material	Wall Thickness (mm)
PE – Polyethylene	0.48

#### **Outer Shield**

#### **Outer Shield Material**

Туре	Outer Shield Material	Coverage
Tape	Aluminum Mylar	125%

#### **Outer Shield Drain Wire AWG**

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC – Tinned Copper

#### **Outer Jacket**

#### **Outer Jacket Material**

Outer Jacket Material	Nom. Wall Thinkness (mm)
PVC – Polivinyl Choloride	0.71

# **Overall Cabling**

Overall Nominal Diameter: 5.6 mm

#### Pair

#### **Pair Color Code Chart**

Number	Color
1	Black & Clear

# **TECHNICAL DATA & SPECIFICATION**



### Mechanical Characteristics (Overall Cable)

Operating Temperature Range	-20°C to 60°C
Temperature Rating	60°C
Max Pulling Tension	28 Kg
Min. Bend Radius	57.15 mm

# Applicable Specifications and Agency Compliance (Overall Cable)

# Applicable Standards

	EU CE Mark (Y/N)	Yes
	EU Directive 2002/95/EC (RoHS) (Y/N)	Yes
Ī	EU RoHS (Y/N)	Yes

# **Electrical Characteristics (Overall Cable)**

Nom. Characteristic Impedance

Impedance (Ohm) 57

Nom. Inductance

Inductance (μH/ft) 0.18

Nom. Capacitance Conductor to Conductor

Capacitance (pF/ft)

Nom. Capacitance Cond. to Other Conductor & Shield

Capacitance (pF/ft)

44

Nom. Conductor DC Resistance

DCR@20°C (Ohm/1000ft)

6.5

Max. Operating Voltage

Voltage 300

Max. Operating Current

Current/Cond. @ 20°C 5,2A

# **TECHNICAL DATA & SPECIFICATION**



### **Part Number**

301-CI9401-0500	1 Pair 18 AWG Shielded Twisted Cable

### **Product Family**

-	
301-CI9401-0500	1 Pair 18 AWG Shielded Twisted Cable
301-CI9402-0500	2 Pair 18 AWG Shielded Twisted Cable
301-CI9404-0500	4 Pair 18 AWG Shielded Twisted Cable

© Alantek Communications USA All Right Reserved.

Alantek® Communications USA 2006. This information provides a general description of product and shall not form part of any contract. Improvement or changes may be made to the product without advanced notification.

Page 3 of 3

Website: <a href="https://Capvienthong.vn/">https://Capvienthong.vn/</a>

Website: https://Capdieukhien.com.vn/

Website: <a href="https://16AWG.com/">https://16AWG.com/</a>

Website: https://18AWG.com/

Địa chỉ: CÁP VIỄN THÔNG HÀ NỘI – Số 490, Trần Khát Chân, phường Phố Huế, quận Hai Bà Trưng, TP. Hà Nội.